

-
- Operating diffuser in small consolidated water treating vessel - by feeding air into raw liquid to prevent clogging of diffusion holes and **wash membrane** cartridges.

L20 ANSWER 90 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD

AN 1997-305806 [28] WPINDEX

DNC C1997-098368

DC D15

PA (KUBI) KUBOTA CORP

QYC 1

PI JP 09117647 A 19970506 (199728)* 4p

ADT JP 09117647 A JP 1995-274606 19951024

PRAI JP 1995-274606 19951024

AN 1997-305806 [28] WPINDEX

AB JP 09117647 A UPAB: 19970709

Operating a diffuser comprises arranging the diffuser under immersion type membrane cartridges for filtration of raw liquid, and feeding aerating air into the raw liquid. During filtration with membrane cartridges, aerating air is fed in amount necessary to treat raw liquid and give air ejecting speed for preventing clogging of diffusing holes and necessary **gas** /liquid mixed rising flow rate for

washing surfaces of **membrane** cartridges. During step-down of filtration with membrane cartridges, aerating air is fed at an air ejecting rate for at least preventing clogging of diffusing holes.

USE - Process is used particularly in a small consolidated type water treating vessel.

ADVANTAGE - Clogging of diffusing holes can be prevented during step-down of filtration with membrane cartridges.

Dwg.1/2

BEST AVAILABLE COPY